



Edgestone™ DX032

Short Form Factor 100GbE Switch for Edge Applications



Celestica's Edgestone DX032 32 port 100GbE switch is a short depth, all front access switch in 2U form factor that is ideally suited for edge computing deployments with limited rack space.

The DX032 provides programmable data plane innovation and can support port level configuration of sub-rates between 10GbE and 50GbE. System maximum of 128 10/25GbE, or 64 50GbE, or 32 100GbE are supported with breakout cables to provide superior large radix switch for TOR or CLOS connectivity. It provides superior low latency and power efficiency in a clean PHYless design, while offering high reliability features such as redundant and hot swappable power supplies and fans in forward and reverse airflow configurations.

Key innovations on the DX032 are its all front access IO, power supplies and fans in a NEBS compliant 288 mm deep chassis. Edgestone DX032 supports current and future network requirements, including dual port access to both the COM-E modular x86-based control plane and the BMC management plane. An ONIE installer is also provided to support third party network operating systems.

FEATURES

Interfaces: 32 QSFP28 100GbE Ports (128 available sub-rate ports), Dual RJ45 CPU Management, Dual RJ45 BMC Management ports, and Console (RJ45) ports, USB (Type A)

Switching Capacity: 3.2Tbps IO Bandwidth, 32M Byte Buffer

Latency: Less than 900ns port to port (cut-through mode, FEC disabled)

IEEE: 802.3az

Datacenter: Dedicated FCoE forwarding engine, IEEE 802.1Qbg and 802.1Qbh, VPLAG, SPB, L2GRE, NVGRE and VXLAN

Telemetry: Improved Instrumentation with Transient Capture Buffer, Packet Timestamp and Buffer Statistics

CPU: Intel Xeon D 1.5Ghz 12-core, 32GB ECC DDR4, Dual 256GB M.2 SSD

Routing Tables: Unified Forwarding Tables: upto 48K MPLS labels, 324K IPv4/208K IPv6 LPM, 128K ACL

Content Aware Processing: Layer 2-7 packet classification, FCoE

Transceivers: QSFP28 upto 4.5W power, SR to 300m, LR to 10km, DAC (to 5m passive)

IEEE1588 & SYNC E TIMING OPTION

Supports IEEE1588

Supports TC and BC mode

Supports SyncE recovery



Enterprise-Class Quality. Cloud Economics.

BMC SYSTEM MANAGEMENT OPTION

DDR4 1GB/SPI 32MB Flash
 Two separate GbE management ports
 Serial over LAN (SOL) enabled
 Supports remote (BIOS/firmware) online upgrading
 IPMI 2.0

LAYER TWO HARDWARE SUPPORTED

802.3ad LACP
 802.1D STP, 802.1w RSTP, 802.1s MSTP
 802.1Q VLAN 4096, SVLAN, PVLAN
 802.1 Q-in-Q double-tagged VLAN
 802.1P L2 Prioritization
 802.1AB LLDP
 802.1x Network Access Control
 IGMP/MLD Snooping
 PBB/PBB-TE
 VM Switching/VEPA/VN-Tag/802.1Qbh
 Mirroring
 Storm Control

LAYER THREE HARDWARE SUPPORTED

Hardware-based IP Forward
 IPv4/v6 Routing Protocols: OSPF, RIP, IS-IS, BGP
 VRF, ECMP/WCMP, VRRP
 VPWS, VPLS, MPLS
 Hardware Based Tunneling: IPv4/v6, GRE, MiM
 IGMPv1/v2/v3
 IP Multicast: PIM-SM, PIM-DM, PIM-SSM
 Hierarchical ECMP

TRAFFIC MANAGEMENT HARDWARE SUPPORTED

Flexible QoS Queuing for UC Packets
 Separate QoS Queues for UC and MC Packets
 (10 each/port)
 SAFC, PFC flow control
 SP, WRR, WDRR Queuing
 ECN, WRED congestion control
 Per-Port DSCP
 ACL, ICAP, ECAP, VCAP

POWER AND COOLING

Under 550W peak consumption with maximum
 optics, 1+1 redundant, hot swap PSUs
 100-240VAC auto-ranging, 47-63Hz, or 40-58VDC
 Power supply options
 5+1 redundant fans, front to back system cooling

DIMENSIONS

Height: 87 mm (3.42") 2 EIA unit
 Width: 442 mm (17.3")
 Depth: 288 mm (11.3")

ENVIRONMENTAL

Operating Temperature: 0°C to 45°C
 Humidity: 5% to 95% non-condensing

APPROVALS

EMC: CN(GB9254-2008), EU(EN55022, EN55024),
 FCC, VCCI, CCC
 Safety: IEC60950-1, GB4943, UL/CSA, CB, CCC
 Environmental: EU RoHS, SVHC requirements of
 REACH, China RoHS, NEBS Level 3

ORDER INFORMATION

DX032-12C32G512-F2B - 12CORE BDE CPU 32GB
 RAM / 512GB SSD, BMC, FRONT TO BACK, AC/HVDC

*Note: All specifications and figures are subject to change
 without prior notice.*