



Titan Server™

4U High-Density Storage Server



The Titan Server is a high-density storage platform with redundant 1U dual-socket servers. The 4U chassis supports up to 90 3.5" or 2.5" SAS/SATA/SSD drives with excellent performance and high availability.

FEATURES

- 4U enclosure designed to fit in 19" wide, 1200 mm deep standard rack
- Cable management assembly (CMA)
- Supports up to 90 3.5" or 2.5" dual ported drives
- 11W max drive power at 35C
- Power control for 12G SAS drive via pin3
- Dual 1U servers, hot-swappable
- Server
 - Dual sockets Intel Xeon/2nd Gen Intel Xeon up to 125W
 - 12 DDR4 DIMMs
 - 1 x OCP Mezz
 - 1 x Custom 4 ports(SFP+) 10GbE Card
 - BMC: AST2500
 - Legacy I/O: VGA, 2xUSB3, 2x 1GbE, 1xRJ45 for BMC
 - Dual M.2 SSD for boot device
 - x16 12G SAS connection to ESM for drive connection
- ESM (Expansion SAS Module)
 - Dual redundant and hot-swappable
 - Four mini-SAS HD ports per ESM for expansion
 - Legacy I/O: one UART via 3.5 mm jack for debug
 - LED: Power LED (green), ESM Fault LED (amber),UID LED (blue)
 - Button: Power button

POWER AND COOLING

- 1300W 80 plus Platinum PSU, 2+2 redundant, hot swap
- 100-127,200-240V AC input, auto ranging, 47-63Hz
- 5 x 80 mm back to back fans, hot-pluggable from top

PHYSICAL DIMENSIONS

- Height: 175.3 mm (6.9")
- Width: 448 mm (17.64")
- Depth: 1175 mm (46.26") w/CMA

ENVIRONMENTAL

- Operating Temperature: 5°C to 35°C
- Non-operating Temperature: -40°C to 60°C
- Humidity: 8% to 85% RH
- Operating Altitude: 950 m (35°C) to 3,048 m (28°C)
- Sound Power: (23+/-2°C) <8.0Bel

APPROVALS

- EMC: EN 55032, CISPR-32 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 47 Part 15 Class A, VCCI V-3 2014 Class A, ICES-003, Issue-004 Class A
- Safety: IEC/EN/UL/ CAN/CSA 60950-1, 62368-1
- Environment: RoHS, REACH, WEEE

Note: All specifications and figures are subject to change without prior notice.



Enterprise-Class Quality. Cloud Economics.

North America: (Toll Free) +1 888 899 9998 | Global: +1 416 448 5800 | contactus@celestica.com | celestica.com