

LokiTM

1U Server



Loki is a high performance server product with Intel® Xeon® Scalable Processors. The 1U chassis supports up to 10 2.5" SAS/SATA/NVMe with excellent performance and high reliability.

FEATURES

Dual Sockets Skylake-SP up to 165W

24 DDR4 RDIMM/LRDIMM up to 1.5TB Cache

NVDIMM is supported

One Internal x8 PCIe Slot for HBA

Up to 2 PCIe Slots for Expansion

• 2x16 FHHL or 2x8 FHHL

1 OCP2.0 card, Connector A+C, Type1

- 4/2 10GbE SFP+ Ports Card
- 4/2 1GbE RJ45 Ports Card

Up to 2 Internal M.2 Slots

Up to 10 2.5" drives are supported

- SAS/SATA/NVMe
- 12Gbps/6Gbps drives

BMC Management (AST2500)

- Standard IPMI2.0
- Dedicated RJ45 for BMC management
- KVM/Virtual Media and SOL
- Cooling management

Hot-swappable PSU and drives

POWER AND COOLING

550W/800W 80 plus Platinum, 1+1 redundant, hot swap PSU

100-127,200-240V AC or HVDC input, auto ranging, $47\sim63$ Hz

6x 4038 FAN for system cooling

PHYSICAL DIMENSIONS

Height: 43.0 mm (1.69", 1U) Width: 448 mm (17.64")

Depth: 760 mm (29.92")

ENVIRONMENTAL

Operating Temperature: 5°C to 35°C

Non-Operating Temperature: -30°C to 60°C

Humidity: 8% to 80% RH

Operating Altitude: 1,000 m at 35°C

Sound Pressure: (23+/-2°C) <65dBA

APPROVALS

EMC: Class A, CISPR 22, FCC, ICES-003, CE, CQC,

VCCI, C-Tic, BSMI

Safety: CB Scheme, UL, cUL, CE, CQC, BSMI, LVD

Environment: RoHS

Note: All specifications and figures are subject to change without prior notice.

