

# Titan™

## 4U High-Density JBOD



Titan is a high density JBOD storage product that supports up to 90 3.5"/2.5" SAS/SATA/SSD drives in 4U enclosure with excellent performance and high availability.

### FEATURES

- 4U enclosure designed to fit in standard 19" wide rack
- Cable management assembly (CMA)
- Supports up to 90 3.5" or 2.5" drives
- SCSI Enclosure Service
- 13W max drive power at 35C
- Power control for 12G SAS drive via pin3
- One optional BMC Card
- Dual redundant ESMS, hot-swappable
- ESM (Expansion SAS Module)
  - Four mini-SAS HD ports per ESM
  - One RJ45 for management
  - One UART via 3.5mm jack
  - LED: Power LED (green), ESM Fault LED (amber), UID LED (blue)
  - Button: Power button

### POWER AND COOLING

- 1200W 80 plus Platinum PSU, 2+2 redundant, hot swap
- 100-127,200-240V AC input, auto ranging, 47~63Hz
- 5 x 80 mm back to back fans, hot-pluggable from the top

### PHYSICAL DIMENSIONS

- Height: 175.3 mm (6.9")
- Width: 446 mm (17.56")
- Depth: 1070 mm (42.12") w/CMA

### ENVIRONMENTAL

- Operating Temperature: 5°C to 35°C
- Non-operating Temperature: -40°C to 60°C
- Humidity: 8% to 85% RH
- Operating Altitude: 3,048 m
- Sound Power: (23+/-2°C) <8.0Bel

### APPROVALS

- EMC: EN 55032, CISPR-32 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 47 CFR Part 15 Class A, VCCI V-3 2014.4 Class A, ICES-003, Issue-004 Class A, GB9254 2008 Class A, GB17625.1-2012
- Safety: IEC/EN/UL/ CAN/CSA 60950-1, GB 4943
- Environment: RoHS, REACH, WEEE

*Note: All specifications and figures are subject to change without prior notice.*



**Enterprise-Class Quality. Cloud Economics.**